

HP E24mv G4 FHD Conferencing Monitor Specifications Table



*Product image may differ from actual product

Display type	IPS
Panel Active Area	20.75 x 11.67 in 52.70 x 29.65 cm
Display size (diagonal)	23.8"
Brightness ¹	250 nits ¹
Contrast ratio	1000:1
Response Ratio	5ms GtG (with overdrive) ¹
Product colour	Black head, silver stand
Aspect ratio	16:9
Native resolution	FHD (1920 x 1080) ¹
Resolutions supported	640 x 480; 720 x 400; 800 x 600; 1024 x 768; 1280 x 720; 1280 x 800; 1280 x 1024; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080
Display features	On-screen controls; Low blue light mode; Dual speakers (2W per channel); Anti-glare; IR webcam; Height Adjust/Tilt/Swivel/Pivot
User controls	Brightness; Exit; Information; Management; Menu; Power; Input control; Image; Color
Input signal	1 VGA; 1 HDMI 1.4; 1 DisplayPort™ 1.2; 4 USB-A 3.1 Gen 1
Display ¹	
Communications	
Camera	Yes, 5MP
Environmental	Operating temperature: 5 to 35°C; Operating humidity: 20 to 80% non-condensing
Power	100 - 240 VAC 50/60 Hz
Power consumption	50 W (maximum), 28 W (typical), 0.5 W (standby)
Dimensions	21.23 x 1.85 x 17.78 in; 53.94 x 4.7 x 35.56 cm (Without stand.)
Weight	14.3 lb; 6.5 kg (With stand.)
Physical security features ²	Security lock-ready
Energy efficiency compliance ³	ENERGY STAR® certified; TCO certified; EPEAT® registered; TCO certified edge; CEL Grade 1
Certification and compliance	Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; GS Mark; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; VCCI; Vietnam MEPS; WEEE; Low blue light; WW application; UAE; Ukraine certificates
What's in the box	Monitor; DisplayPort™ cable; HDMI cable; USB Type-A to B cable; Doc-kit; AC power cord